

# CHECKLIST FOR PAINT CHIP REPAIR

## 01 ASSESSMENT

Check for clear coat scratches vs paint chips.

Note the size and depth.

Mark the location.

Be attentive to vertical planes and sharp angles.

## 03 APPLICATION

Mix the base color and clear coat in a dixie cup.

Remove applicator tip from touch-up stick.

Should now resemble a toothpick.

Apply a tiny amount of paint to the tip.

Dab the chip, leaving a small bulb of paint.

Dry the bulb using the heat gun for 2-5 minutes.

Let cure for 24 hours.

## 02 PREPARATION

Glue a small circle of sand paper to pencil's eraser tip.

Clean out the chip area by scrubbing or twirling the eraser tip.

Wax the chip and the surrounding area.

Remove wax from chip using touch-up stick and alcohol.

## 04 LEVELING

Wrap the 2000 grit sand paper around the pad.

Wet the surface and the sand paper.

Work the area until the crown has been leveled.

Compound and polish the area to restore the shine.

Apply sealant and wax for protection.

### RECOMMENDED TOOLS

Touch-up Sticks  
2000 Grit Sand Paper  
Carnauba Wax  
Rubbing Alcohol  
Micro Fiber Towel  
Heat Gun  
#2 Pencil  
Crazy Glue  
Base Color Touch-up\*  
Clear Coat Touch-up\*  
Dixie Cup  
Flat Card/Pad

\* Water Based Paint